

Revision date 06-Dec-2022

BOSTIK V60 SILICONE BLACK Revision Number 1.02

Revision Number 1.02 Supersedes Date: 07-Nov-2022

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name BOSTIK V60 SILICONE BLACK

Product Code(s) 30804555 30804555

Other means of identification

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Sealant

Uses advised against No information available

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd 51-71 High Street, Thomastown Victoria Australia

Tel: 613 9279-9333 Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1B - (H317)

Label elements

Exclamation mark



Australia - EN Page 1/9

BOSTIK V60 SILICONE BLACK

Revision Number 1.02 Supersedes Date: 07-Nov-2022

Revision date 06-Dec-2022

Signal word

WARNING

Hazard statements

H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation

The real education control of a minument

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace

Wear protective gloves/clothing and eye/face protection

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of water and soap

If skin irritation or rash occurs: Get medical advice/attention Take off contaminated clothing and wash it before reuse

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number Not applicable

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

<u>Mixture</u>

Chemical name	CAS No	Weight-%
2-Butanone, O,O',O"-(methylsilylidyne)trioxime	22984-54-9	0 - <10
Butan-2-one O,O',O"-(vinylsilylidyne)trioxime	2224-33-1	0 - <10
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26

Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact Wash with soap and water. May cause an allergic skin reaction. In the case of skin

Australia - EN Page 2/9

BOSTIK V60 SILICONE BLACK

Revision Number 1.02 Supersedes Date: 07-Nov-2022

irritation or allergic reactions see a physician.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

Revision date 06-Dec-2022

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

Most important symptoms and effects, both acute and delayed

Symptoms None known.

Indication of any immediate medical attention and special treatment needed

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable extinguishing media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

Specific hazards arising from the chemical

Specific hazards arising from the

Thermal decomposition can lead to release of irritating gases and vapors.

chemical

Hazardous combustion products Nitrogen oxides (NOx). Silicon oxides.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautionsDo not get in eyes, on skin, or on clothing. Use personal protective equipment as

required. Ensure adequate ventilation.

Other information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Australia - EN Page 3/9

BOSTIK V60 SILICONE BLACK

Revision Number 1.02 Supersedes Date: 07-Nov-2022

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact

with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product.

Revision date 06-Dec-2022

Take off contaminated clothing and wash before reuse.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work. Take off contaminated clothing and wash it before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feeding stuffs.

Recommended storage

temperature

Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

Incompatible materials Strong oxidizing agents.

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released

upon curing.

Appropriate engineering controls

Engineering controls Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear suitable protective clothing.

Hand protection Wear suitable gloves.

Respiratory protection Organic gases and vapors filter conforming to EN 14387. White. Brown.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Paste / Gel Liquid Appearance Very viscous Paste

Color Black Odor Slight

Odor threshold No information available

Property Values Remarks • Method

pH No data available Not applicable Insoluble in water

Australia - EN Page 4/9

BOSTIK V60 SILICONE BLACK

Revision Number 1.02 Supersedes Date: 07-Nov-2022

Revision date 06-Dec-2022

pH (as aqueous solution)

Melting point / freezing point

Initial boiling point and boiling

No data available

No data available

range

Flash point > 110 °C CC (closed cup)

Evaporation rateNo data available **Flammability**Not applicable for liquids.

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapor pressureNo data availableRelative vapor densityNo data available

Relative density 1.02

Water solubility
Solubility(ies)
Partition coefficient
Autoignition temperature
No data available

Explosive propertiesNo information available **Oxidizing properties**No information available

Other information

Solid content (%) No information available

Density No information available

VOC content No information available

Section 10: Stability and reactivity

Reactivity

Reactivity Product cures with moisture.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze.

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

Australia - EN Page 5/9

BOSTIK V60 SILICONE BLACK

Revision Number 1.02 Supersedes Date: 07-Nov-2022

products curing. 2-Butanone, oxime.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact May cause sensitization by skin contact. Specific test data for the substance or mixture is

not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause irritation. Prolonged contact

Revision date 06-Dec-2022

may cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg

ATEmix (dermal) 22,316.141

Component Information

Chemical name Oral LD50		Dermal LD50	Inhalation LC50
2-Butanone,	LD50 = 2463 mg/Kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	-
O,O',O''-(methylsilylidyne)trioxi	(OECD 401)	(OECD 402)	
me			
Butan-2-one	LD50 > 2000 mg/kg (Rattus)	LD50 > 2009 mg/kg (Rattus)	-
O,O',O"-(vinylsilylidyne)trioxime	OECD 425	OECD 402	

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No information available.

Reproductive toxicity No information available.

STOT - single exposure No information available.

Australia - EN Page 6/9

BOSTIK V60 SILICONE BLACK

Revision Number 1.02 Supersedes Date: 07-Nov-2022

Revision date 06-Dec-2022

STOT - repeated exposure No information available.

Aspiration hazard No information available.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
2-Butanone, O,O',O"-(methylsilylidyn e)trioxime 22984-54-9		EC50 (96h) >120 mg/L (Oncorhynchus mykiss)Freshwater static (OECD guideline 203)	-	EC50 (48h) > 120 mg/L (Daphnia magna) OECD 202
Butan-2-one O,O',O"-(vinylsilylidyne)t rioxime 2224-33-1	EC50 (72h) = 16 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h)> 120 mg/L (Oncorhynchus mykiss) OECD 203	-	EC50 (48h) > 120 mg/L (Daphnia magna) OECD 202

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
2-Butanone, O,O',O"-(methylsilylidyne)trioxime 22984-54-9	1.69
Butan-2-one O,O',O"-(vinylsilylidyne)trioxime 2224-33-1	1.69

Mobility

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

Section 14: Transport information

Australia - EN Page 7/9

BOSTIK V60 SILICONE BLACK

Revision Number 1.02 Supersedes Date: 07-Nov-2022

Revision date 06-Dec-2022

ADG Not regulated

Not regulated IATA

Not regulated **IMDG**

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated Classified as a scheduled poison according to the Standard for Uniform Scheduling of

Medicines and Poisons (SUSMP)

Poison Schedule Number Not applicable

International Inventories

Listed AIIC **NZIoC** Listed **ENCS** Not Listed **IECSC** Listed Listed **KECL PICCS** Listed

Legend:

AIIC - Australian Inventory of Industrial Chemicals

NZIoC - New Zealand Inventory of Chemicals

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Australia - EN Page 8/9

BOSTIK V60 SILICONE BLACK

Revision Number 1.02 Supersedes Date: 07-Nov-2022

Revision date 06-Dec-2022

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 06-Dec-2022

Revision Note

SDS sections updated. 3. 9. 11.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

C Carcinogen

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

Australia - EN Page 9/9