NFK GLAZING & INDUSTRIAL SUPPLIES Professional Products for the Glass & Glazing industry

Creation Date: November, 2016 This version issued: February, 2022

Page 1

MATERIAL SAFETY DATA SHEET

INOX-mx3 Aerosol

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Chemical nature	Oil blend dispensed as an aerosol
Trade Name	INOX-mx3 Aerosol
Product Code	21-INNOX (300 g)
Product Use	Anti-corrosion, anti-moisture penetrating oil
Company	NFK Glazing & Industrial Supplies
Contact phone	+61 7 3343 3377
Emergency phone Poisons Information Centre:	1800 033 111, 13 11 26 from anywhere in Australia

NFK Glazing
& Industrial SuppliesImage: Second Control of C

2. HAZARDS IDENTIFICATION

Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of SWA. Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: None allocated.

None allocated.

ADG Classification: Class 2.1: Flammable gases.

UN Number: 1950, AEROSOLS.

GHS Signal word: DANGER.

Flammable aerosols Category 2

HAZARD STATEMENT

H223: Flammable aerosol. H229: Pressurised container: may burst if heated.

PREVENTION

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P211: Do not spray on an open flame or other ignition source.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical ventilating, lighting and other equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P271: Use only outdoors or in a well ventilated area.

P280: Wear protective gloves, protective clothing and eye or face protection.

NFK Glazing & Industrial Supplies	 28 Devlan Street, Mansfield, QLD 4122 	 42 Tacoma Circuit, Canning Vale, WA 6155
	© 07 3343 3377	08 9455 3866
www.nfk.com.au	🖻 sales@nfk.com.au	🖻 wasales@nfk.com.au



RESPONSE

P362: Take off contaminated clothing and wash before reuse. P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water. P372: Explosion risk in case of fire.

P381: Eliminate all ignition sources if safe to do so.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam. Water fog or fine spray is the preferred medium for large fires.

STORAGE

P402: Store in a dry place.

P403: Store in a well-ventilated place.

P410+P412: Store below 30°C, protect from direct sunlight and do not expose to temperatures exceeding 50°C.

DISPOSAL

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

Statement of Hazardous Nature (New Zealand)

HSR002515 Aerosols Flammable Group Standard 2020.

DG Classification:

Classified as a Dangerous Good for transport in accordance with the Land Transport Rule Dangerous Goods 2005 and NZS 5433:2007.

EMERGENCY OVERVIEW

Physical Description & Colour:

Aerosol, dispensed product is a clear light tan liquid.

Odour:

Mild odour.

Major Health Hazards:

No significant risk factors have been found for this product.

NFK Glazing & Industrial Supplies

www.nfk.com.au

28 Devlan Street, Mansfield, QLD 4122

07 3343 3377

Sales@nfk.com.au

 42 Tacoma Circuit, Canning Vale, WA 6155

08 9455 3866

🖻 wasales@nfk.com.au

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS No	Conc, %	TWA (mg/m3)	STEL (mg/m3)
Butane	106-97-8	<30	1900	not set
Propane	74-98-6	<10	not set	not set
Ketone	secret	<5	100	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

4. FIRST AID MEASURES

GENERAL INFORMATION:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 11 26 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation:

No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

NFK Glazing & Industrial Supplies

www.nfk.com.au

- 28 Devlan Street, Mansfield, QLD 4122
- 07 3343 3377
- Sales@nfk.com.au

 42 Tacoma Circuit, Canning Vale, WA 6155

- 08 9455 3866
- Swasales@nfk.com.au

Skin Contact:

Irritation is unlikely. However, if irritation does occur, flush with lukewarm, gently flowing water for 5 minutes or until chemical is removed.

Eye Contact:

Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed, while holding the eyelid(s) open. Obtain medical advice immediately if irritation occurs. Take special care if exposed person is wearing contact lenses.

Ingestion:

If product is swallowed or gets in mouth, do NOT induce vomiting; wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

5. FIRE FIGHTING MEASURES

Fire and Explosion Hazards:

The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media:

In case of fire, use carbon dioxide, dry chemical, foam. Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses.

Fire Fighting:

If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.



Autoignition temperature: No data.

Flammability Class: No data.

6. ACCIDENTAL RELEASE MEASURES

Accidental release:

This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

7. HANDLING AND STORAGE

Handling:

Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage:

Store in a cool (below 30°C), well ventilated area. Protect from direct sunlight. Make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep more than 25kg of flammable gases, you are probably required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

NFK Glazing & Industrial Supplies

www.nfk.com.au

28 Devlan Street, Mansfield, QLD 4122

07 3343 3377

🖻 sales@nfk.com.au

 42 Tacoma Circuit, Canning Vale, WA 6155

08 9455 3866

🖸 wasales@nfk.com.au

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: AS/NZS 1715

Protective Gloves: AS 2161

Occupational Protective Clothing: AS/NZS 4501 set 2008

Industrial Eye Protection: AS1336 and AS/NZS 1337

Occupational Protective Footwear: AS/NZS2210

SWA Exposure Limits	TWA (mg/m3)	STEL (mg/m3)
Butane	1900	not set
Ketone	100	not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation:

This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection:

Eye protection such as protective glasses or goggles is recommended when this product is being used.

Skin Protection:

The information at hand indicates that this product is not harmful and that normally no special skin protection is necessary. However, we suggest that you routinely avoid contact with all chemical products and that you wear suitable gloves (preferably elbow-length) when skin contact is likely.

NFK Glazing & Industrial Supplies

www.nfk.com.au

- 28 Devlan Street, Mansfield, QLD 4122
- 07 3343 3377
- Sales@nfk.com.au
- 42 Tacoma Circuit, Canning Vale, WA 6155
- 08 9455 3866
- 😋 wasales@nfk.com.au

Protective Material Types:

There is no data that enables us to recommend any type except that it should be impermeable.

Respirator:

Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Description & colour	Aerosol, dispensed product is a clear light tan liquid
Odour	Mild odour
Boiling Point	Not available
Flash point	Propellant is flammable. Dispensed product has a flash point of 182°C when propellant gas has dissipated
Upper Flammability Limit	Not available
Lower Flammability Limit	Not available
Freezing/Melting Point	-18°C
Volatiles	No data
Vapour Pressure	<6 kPa (dispensed product)
Vapour Density	No data
Specific Gravity	0.840 (dispensed product)
Water Solubility	Negligible
рН	No data
Volatility	No data
Odour Threshold	No data



PHYSICAL AND CHEMICAL PROPERTIES (1.2)

Evaporation Rate	No data
Coeff Oil/water Distribution	No data
Particle Characteristics	Not applicable for liquids

10. STABILITY AND REACTIVITY

Reactivity:

This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid:

Store below 30°C, protect from direct sunlight and do not expose to temperatures exceeding 50°C. Keep containers tightly closed. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed. Protect this product from light.

Incompatibilities:

Strong oxidising agents, flammable liquids, corrosive materials.

Fire Decomposition:

Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation:

This product will not undergo polymerisation reactions.



11. TOXICOLOGICAL INFORMATION

Local Effects:

Target Organs:

There is no data to hand indicating any particular target organs.

11.1 CLASSIFICATION OF HAZARDOUS INGREDIENTS

Ingredient		
Propane	Butane	Ketone
 Flammable gas - category 1 Gas under pressure 	 Flammable gas – category 1 Gases under pressure 	 Flammable liquid - category 3 Acute toxicity - category 4
Health Hazard Statement Codes		
H220	H220	

11.2 POTENTIAL HEALTH EFFECTS

Inhalation:

Short Term Exposure:

Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort. Intentional misuse by deliberately concentrating and inhaling contents of aerosol containers can be harmful or fatal.

Long Term Exposure:

No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure:

Major health effect from this product is misuse of the aerosol function. If sprayed continuously on skin or in eyes, it can cause frostbite.

Long Term Exposure:

No data for health effects associated with long term skin exposure.

NFK Glazing & Industrial Supplies

www.nfk.com.au

28 Devlan Street, Mansfield, QLD 4122

07 3343 3377

- Sales@nfk.com.au
- 42 Tacoma Circuit, Canning Vale, WA 6155

08 9455 3866

🖻 wasales@nfk.com.au

Eye Contact:

Short Term Exposure:

If sprayed directly in the eye, this product will irritate. If spraying is prolonged, it may cause damage through frostbite.

Long Term Exposure:

No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure:

Significant oral exposure is considered to be unlikely. This product, while believed to be not harmful, is likely to cause headache and gastric disturbance such as nausea and vomiting if ingested in significant quantities. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

<u>Long Term Exposure:</u> No data for health effects associated with long term ingestion.

Carcinogen Status:

<u>SWA:</u> No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC:

Ketone is Class 3 - unclassifiable as to carcinogenicity to humans. See the IARC website for further details. A web address has not been provided as addresses frequently change.

NFK Glazing	 28 Devlan Street, 	 42 Tacoma Circuit,
& Industrial Supplies	 28 Devlan Street, Mansfield, QLD 4122 	42 Tacoma Circuit, Canning Vale, WA 6155
	🔕 07 3343 3377	08 9455 3866
www.nfk.com.au	🖻 sales@nfk.com.au	😋 wasales@nfk.com.au

12. ECOLOGICAL INFORMATION

Insufficient data to be sure of status.

13. DISPOSAL CONSIDERATIONS

Disposal:

Aerosol containers can be disposed of in household waste or, in some areas, recycled, when empty. If it is necessary to dispose of unused product, or containers which are not empty, a specialist waste disposal company should be used. Never crush, puncture or burn aerosol containers, even when empty.

14. TRANSPORT INFORMATION

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number: 1950, AEROSOLS Hazchem Code: 2YE Special Provisions: 63, 190, 277 Limited quantities: ADG 7 specifies a Limited Quantity value of 1000mL for this class of product. Dangerous Goods Class: Class 2.1: Flammable gases. Packing Group: Not set Packing Instruction: P003

Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

NFK Glazing & Industrial Supplies

www.nfk.com.au

- 28 Devlan Street, Mansfield, QLD 4122
- 07 3343 3377
- Sales@nfk.com.au

- 42 Tacoma Circuit, Canning Vale, WA 6155
- 08 9455 3866
- 😋 wasales@nfk.com.au

15. REGULATORY INFORMATION

AIIC:

All of the significant ingredients in this formulation are compliant with AICIS regulations.

New Zealand:

HSR002515 Aerosols Flammable Group Standard 2020

16. OTHER INFORMATION

This SDS contains only safety-related information. For other data see product literature.

Acronyms.

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition)
AIIC	Australian Inventory of Industrial Chemicals
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number



THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE. IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

<u>Australia</u>: This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (July 2020) and GHS Revision 7

New Zealand: HSNO Approved Code of Practice: Preparation of Safety Data Sheets. New Zealand Chemical Industry Council September 2006.

NFK Glazing & Industrial Supplies	28 Devlan Street, Mansfield, QLD 4122	 42 Tacoma Circuit, Canning Vale, WA 6155
	07 3343 3377	🔕 08 9455 3866
www.nfk.com.au	🕒 sales@nfk.com.au	🖻 wasales@nfk.com.au