



NFK DOUBLE-SIDED MIRROR MOUNTING TAPE



- Acrylic (solvent-based) adhesive coated on both sides
- High grab tack, shear strength adhesive that provides bonding security
- Good resistance to wearing, oxidation, UV and a wide temperature range

Typical Applications

Flexible soft foam can seal up effectively against water, dust and light, suitable for glazing and mirror mounting.

Typical Physical Properties

Property	Value	Test Method
Colour:	White	
Carrier:	3.0mm 3 PCF PE foam	
Thickness:	3.0 ± 0.2mm	
Liner:	4 mil blue colour polyolefin release liner	
Tensile Strength:	Over 25 kg / 25 mm x 25 mm	
Loop tack:	4.5 kg / 25 mm (foam broken)	FINAT-9
Shear strength:	Over 24 hrs with 1.0 kg sandwich 2 stainless steel plates loading on 25 mm x 25 mm at 25°C	
Heat resistance:	Over 24 hrs with 0.5 kg sandwich 2 stainless steel plates loading on 25 mm x 25 mm at 80°C	
Peel Adhesion:	2.8 kg / 25 mm (foam broken)	PSTC-3
Service Temperature:	- 20°C ~ 90°C	

All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty. It's essential that the user should evaluate the product for a period of time to determine whether it is fit for a particular purpose and suitable for the user's method of application.