



NFK DOUBLE-SIDED MIRROR MOUNTING TAPE



- Acrylic (solvent-based) adhesive coated on both sides
- High grab tack, shear strength adhesive that provides bonding security
- Good resistance to wearing, oxidation, UV and a wide temperature range

Typical Applications

Flexible soft foam can seal up effectively against water, dust and light, suitable for glazing and mirror mounting.

Typical Physical Properties

Property	Value	Test Method
Colour:	White	
Carrier:	0.8mm 6 PCF PE foam	
Thickness:	0.8 ± 0.1 mm	
Liner:	4 mil blue colour polyolefin release liner	
Tensile: Strength	Over 30kg/25mm x 25mm	
Loop tack:	3.0kg/25mm	FINAT-9
Shear strength:	Over 24hrs with 2.0kg sandwich 2 stainless steel plate loading on 25mm x 25mm at 25°C	
Heat resistance:	Over 24hrs with 1.0kg sandwich 2 stainless steel plate loading on 25mm x 25mm at 80°C	
Peel Adhesion:	1.6kg/25mm	PSTC-3
Service Temperature:	-20° C to 100°C	

All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty. It's essential that the user should evaluate the product for a period of time to determine whether it is fit for a particular purpose and suitable for the user's method of application.