



CLOSED-CELL PVC FOAM TAPE



- Closed-cell PVC foam Tape 7300 Series with adhesive on both sides
- High-tack acrylic adhesive
- The closed cell structure completely seals out air, moisture and dust
- It provides a watertight seal when compressed 30% or more
- Low thermal conductivity reduces heat transfer
- Excellent resistance to aging

Applications:

- Designed for use in commercial and residential glazing systems
- Ideal for marine window glazing applications.

Typical Physical Properties

Property	Value
Thickness	3.2mm
Width options	9mm, 12mm and custom
Maximum width:	Up to 1250mm
Roll length	20Mtr
Density: kg/m ³	220-300
Tape color	Black, Blue PE liner
Force to compress at 30%	168N/CM ² - 6mm
Compression set:	10% max
Hardness:	55-75 (shore 00)
Elongation:	150% min
Watertight seal at:	20% compression
Water absorption:	8% by volume
Thermal conductivity:	0.16 kcal
Temperature resistance:	-50deg. to 60deg. C

NOTE:

When applying pressure sensitive adhesive tapes, do not touch adhesives, ensure that surfaces are free from oil or other surface contaminants such as powder, dust or release agents.

All information and recommendations has been based on research of the Producer and is believed to be reliable, but does not constitute a warranty.

All TAPE CONVERTING products are sold with the understanding that the buyer will independently determine the suitability of the product.