



CLOSED-CELL PVC FOAM TAPE



- Closed-cell PVC foam Tape Norseal® with a pressure-sensitive adhesive on both sides
- Excellent resistance to weathering, oxidation and ultraviolet light
- Ideal for glazing joints with high movement
- Proven Performance Fast and Easy Application
- Compatible with most glazing components
- Exceeds the requirements of AAMA 810.1
- Provides uniform sight lines without hand tooling, oozing or cold flow of sealant
- easy-peel paper or poly liner protects the adhesive faces prior to installation while preventing stretching during application
- Norseal V980/V990 is perfect for sealing out water, dust and light, particularly in joints with a high degree of movement.
- The high-density foam provides strength, making it ideal for die-cutting operations.
- Norseal's outstanding resistance exposure further enhances its long-lasting seal

TYPICAL APPLICATIONS

- Interior/Exterior glazing sealant for metal, wood and vinyl sash systems
- Residential/Commercial window glazing
- Heating and ventilation duct systems
- Commercial refrigeration glazing
- Vibration damping
- Marine glazing
- Die-cut gaskets
- Store display cases



Typical Physical Properties

The length of the rolls varies depending on the thickness of the material. Data is intended as a guide only and is presented without guarantees and without the assumption of liabilities resulting from the information provided. Parameter values are not guaranteed and will differ from lot to lot.

Test Method	Property	Value
	Thickness options	1.6mm, 3.2mm, 4.8mm, 6,4mm
	Width options	9mm, 12mm and custom
	Roll length	15,2 Mtr, 30,5Mtr, 61Mtr
ASTM D-1667	Density: kg/m ³	240
	Tape color	Black
AAMA 810.1	Force to compress psi (kPa)	11 (76)
AAMA 810.1	Compression Deflection psi (kPa)	7.8 (54)
AAMA 810.1	Compression Set %, based on 25% comp.	0.6
AAMA 810.1	Water Absorption, % by weight	1,3%
AAMA 810.1	Water Penetration %	3
AAMA 810.1	Tensile Adhesion psi (kPa)	60 (414)
	Recommended service temperature (C)	-34deg to +82deg
	Recommended application temperature (C)	minimum 7deg
	Peel Adhesion psi (kPa)	5 (876)

Please note: NFK Glazing & Industrial Supplies cannot anticipate or control every potential application. We strongly recommend testing this product under actual application conditions prior to use. The product contains plasticizer, which may adversely affect some plastics.