



## WATERPROOF MASKING TAPE



- Natural rubber solvent-based adhesive provides good adhesion on uneven surfaces and heat resistance up to 90°C (30 min)
- Easy removal without adhesive residue, if it is removed as soon as the paint is dry
- Water-resistant saturated paper backing provides conformance to most shaped surfaces and high resistance to moisture and water
- Compatible with most common paints and lacquers
- Removable without breaking
- Hand tearable

## Typical Applications

Waterproof masking tape is widely used for car repair applications as well as for wall-painting on building and construction sites and industrial use.

## Typical Physical Properties

Property	Value	Method
Colour	Yellow	
Backing	63 g/m <sup>2</sup> waterproof saturated crepe paper; yellow	
Adhesive	Natural rubber and resins solvent based	
Total thickness	0.130mm	PSTC 133
Adhesion to steel, N/25mm	4.8	PSTC 101
Tensile strength MD, N/25mm	90	PSTC 131
Elongation at break	8%	PSTC 131
Temp. Resistance	90°C (30 min)	

Typical values are not intended to be used for specification purposes. Technical data is believed to be true and accurate but they are not guaranteed. We recommend the purchaser test the fitness and suitability for the intended use for all applications. The above data derive from tests effected in our laboratories, selected from standard production runs, and do not imply any suitability guarantee. The user must preliminarily verify the suitability of the product for the intended specific application use.