

MATERIAL SAFETY DATA SHEET HAZARDOUS, NON-DANGEROUS GOODS

ISSUED: 2023-01-19 VERSION: 2.0

1.	Chemical Product and Company Identification
MSDS Name:	GSA Pro Seal 500
Product Code:	29-001C
Recommended use:	Silicone elastomer
Company:	NFK Glazing & Industrial Supplies
Contact phone:	+61 7 3343 3377
Emergency phone:	1800 033 111

NFK Glazing & Industrial Supplies 28 Devlan Street, Mansfield, QLD 4122
07 3343 3377
sales@nfk.com.au



ww.nfk.com.au

2. COMPOSITION, INFORMATION ON INGREDIENTS

CAS#	CHEMICAL NAME	PERCENT
2224-33-1	2-Butanone, O,O',O''- (ethenylsilylidyne) trioxime	0.1 - 1.0 %
	Ingredients determined to be Non-Hazardous	Balance
		100%

3. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of Safe Work Australia GHS 7. Signal Word Warning **Hazard Classifications** Eye Damage/Irritation - Category 2A Sensitisation - Skin - Category 1B **Hazard Statements** H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Prevention Precautionary Statements

P102 Keep out of reach of children. P103 Read carefully and follow all instructions. **P261** Avoid breathing dust, fume, gas, mist, vapours or spray. P264 Wash hands, face and all exposed skin thoroughly after handling. **P272** Contaminated work clothing should not be allowed out of the workplace. **P280** Wear protective gloves/protective clothing, gloves, eye/face protection and a suitable respirator.

Response Precautionary Statements

P101 If medical advice is needed, have a product container or label at hand. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P363 Wash contaminated clothing before reuse.

Storage Precautionary Statement

Not allocated

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations. Poison Schedule: Not Applicable

DANGEROUS GOODS CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

NFK Glazing & Industrial Supplies

0	28 Devlan Street, Mansfield, QLD 4122
٩	07 3343 3377
9	sales@nfk.com.au





4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove the victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen the remaining clothing. Allow the patient to assume the most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if the effects persist.

Skin Contact: Effects may be delayed. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. **Eye contact:** If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

PPE for First Aiders: Wear safety shoes, overalls, gloves, chemical goggles, dust mask. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash your hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed.

5. FIRE FIGHTING MEASURES

Hazchem Code: Not applicable.

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol-resistant foam, standard foam, or dry agent (carbon dioxide, dry chemical powder). **Specific hazards:** Combustible material.

Fire fighting further advice: On burning or decomposing may emit toxic fumes. Firefighters are to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services. **Dangerous Goods - Initial Emergency Response Guide No: Not applicable**

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of dust.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for spills.

NFK Glazing & Industrial Supplies

	28 Devlan Street, Mansfield, QLD 4122 07 3343 3377
\mathbf{x}	sales@nfk.com.au



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Form: Paste Colour: Colourless Odour: Faint Solubility: Insoluble in water Specific Gravity: N Av Relative Vapour Density (air=1): N App Vapour Pressure: N App Flash Point (°C): 81 Flammability Limits (%): N Av Autoignition Temperature (°C): 450 Melting Point/Range (°C): N Av Boiling Point/Range (°C): N Av PH: N Av Viscosity: N App Total VOC (g/Litre): N Av

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes. Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects are expected if the product is handled by this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are: Acute Effects

- Inhalation: Material may be an irritant to mucous membranes and the respiratory tract.
- Skin contact: Contact with the skin may result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.
- Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.
- Eye contact: An eye irritant. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

Acute toxicity

- Inhalation: This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): LC50 > 5.0 mg/L for dust.
- Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): LD50 > 2,000 mg/Kg bw
- Ingestion: This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): LD50 > 2,000 mg/Kg bw
- Corrosion/Irritancy: Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes). Skin: This material has been classified as not corrosive or irritating to the skin.
- Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser. Skin: This material has been classified as a Category 1B Hazard (skin sensitiser).
- Aspiration hazard: This material has been classified as not an aspiration hazard.
- Specific target organ toxicity (single exposure): This material has been classified as not a specific hazard to target organs by a single exposure.

Chronic Toxicity

- Mutagenicity: This material has been classified as not a mutagen.
- Carcinogenicity: This material has been classified as not a carcinogen.
- Reproductive toxicity (including via lactation): This material has been classified as not a reproductive toxicant.
- Specific target organ toxicity (repeat exposure): This material has been classified as not a specific hazard to target organs by repeat exposure.

NFK Glazing & Industrial Supplies



 42 Tacoma Circuit, Canning Vale, WA 6155
08 9455 3866
wasales@nfk.com.au

ww.nfk.com.au

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

Long-term aquatic hazard: This material has been classified as not hazardous for chronic aquatic exposure. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log Kow < 4. **Ecotoxicity:** No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS. If possible material and its container should be recycled. If material or container cannot be recycled, dispose of in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. REGULATORY INFORMATION

This material is not subject to the following international agreements: Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants) The Rotterdam Convention (Prior Informed Consent) Basel Convention (Hazardous Waste) International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

- The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): Not Applicable.
- AICIS Status: All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC).

NFK Glazing & Industrial Supplies 28 Devlan Street, Mansfield, QLD 4122
07 3343 3377
sales@nfk.com.au



ww.nfk.com.au

16. OTHER INFORMATION

Reason for issue: Revised

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer and supplier will not be held responsible for any unauthorised use of this information or for any modified or altered versions. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for product as sold is subject to our standard terms and conditions.

NFK Glazing & Industrial Supplies

ww.nfk.com.au

 28 Devlan Street, Mansfield, QLD 4122
07 3343 3377
sales@nfk.com.au

