

Issued: 8 October 2021 Version: 1.0 Reference No: SELNZ7EN001164

MATERIAL SAFETY DATA SHEET

Hazardous, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name:	CONTRACTORS SERIES
Recommended use:	Adhesive
Product Code:	29-40, 29-4009, 29-4013, 29-4017
Supplier:	NFK Glazing & Industrial Supplies Ltd
Address:	28 Devlan Street, Mansfield, QLD 4122
Contact phone:	+61 7 3343 3377
Emergency phone:	1800 033 111

NFK Glazing & Industrial Supplies

www.nfk.com.au

28 Devlan Street, Mansfield, QLD 4122

07 3343 3377

Sales@nfk.com.au

 42 Tacoma Circuit, Canning Vale, WA 6155
 08 9455 3866

🖻 wasales@nfk.com.au

2. HAZARDS IDENTIFICATION

This material is hazardous according to the criteria of EPA New Zealand GHS 7.

EPA Group Standard:

HSR002544 - Construction Products (Subsidiary Hazard) Group Standard 2020

Signal Word

Warning

Hazard Classifications

Skin Corrosion/Irritation - Category 2 Serious Eye Damage/Irritation - Category 2

Hazard Statements

H315 Causes skin irritation. H319 Causes serious eye irritation.

Prevention Precautionary Statements

P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P264 Wash hands, face and all exposed skin thoroughly after handling.
P280 Wear protective gloves/protective clothing including eye/face protection and suitable respirator.

Response Precautionary Statements

P101 If medical advice is needed, have product container or label at hand.
P302+P352 IF ON SKIN: Wash with plenty of water and soap.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362 Take off contaminated clothing.

Storage Precautionary Statement

Not allocated



www.nfk.com.au

- 28 Devlan Street, Mansfield, QLD 4122
- 07 3343 3377
- Sales@nfk.com.au



- 08 9455 3866
- 😋 wasales@nfk.com.au



Disposal Precautionary Statement

Not allocated

DANGEROUS GOOD CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
		1 - 10 % (w/w)
Acetoxysilane	4253-34-3	
		Balance
Ingredients determined to be non-hazardous or below reporting limits		
		100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation:

Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin Contact:

If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital.

NFK Glazing & Industrial Supplies

www.nfk.com.au

- 28 Devlan Street, Mansfield, QLD 4122
- 07 3343 3377
- Sales@nfk.com.au

- 42 Tacoma Circuit, Canning Vale, WA 6155
- 08 9455 3866
- 😂 wasales@nfk.com.au

Eye contact:

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion:

Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

PPE for First Aiders:

Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician:

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Hazchem Code:

Not applicable. Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards:

Combustible material.

Fire fighting further advice:

On burning or decomposing may emit toxic fumes. Fire fighters to wear selfcontained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.



6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of dust. Work up wind or increase ventilation. Cover with damp absorbent (inert material, sand or soil). Sweep or vacuum up, but avoid generating dust. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No:

Not applicable

7. HANDLING AND STORAGE

Handling:

Avoid eye contact and skin contact. Avoid inhalation of dust.

Storage:

Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for spills.

NFK Glazing	 28 Devlan Street, Mansfield, QLD 4122 	42 Tacoma Circuit, Canning Vale, WA 6155
& Industrial Supplies	© 07 3343 3377	08 9455 3866
www.nfk.com.au	Sales@nfk.com.au	🕒 wasales@nfk.com.au

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

No value assigned for this specific material by WorkSafe New Zealand.

Biological Limit Values:

As per the WorkSafe New Zealand the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures:

Natural ventilation should be adequate under normal use conditions.

Personal Protection Equipment:

SAFETY SHOES, OVERALLS, GLOVES, SAFETY GLASSES.

Wear safety shoes, overalls, gloves, safety glasses. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Hygiene measures:

Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of dust. Ensure that eyewash stations and safety showers are close to the workstation location.

NFK Glazing & Industrial Supplies	 28 Devlan Street, Mansfield, QLD 4122 	 42 Tacoma Circuit, Canning Vale, WA 6155
	🔇 07 3343 3377	08 9455 3866
www.nfk.com.au	🖻 sales@nfk.com.au	🖻 wasales@nfk.com.au

9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Paste
Colour:	N Av
Odour:	Acetic acid
Solubility:	Insoluble in water
Specific Gravity:	0.93 - 1.13
Relative Vapour Density (air=1):	>1
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	>93 (CC)
Flammability Limits (%):	N Арр
Autoignition Temperature (°C):	N Av
Melting Point/Range (°C):	N Av
Boiling Point/Range (°C):	>35
pH:	N Арр
Viscosity:	N Av
Total VOC (g/Litre):	N Av

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

 28 Devlan Street, Mansfield, QLD 4122 	42 Tacoma Circuit, Canning Vale, WA 6155
07 3343 3377	08 9455 3866
Sales@nfk.com.au	🕒 wasales@nfk.com.au
	07 3343 3377

10.STABILITY AND REACTIVITY

Chemical stability:

This material is thermally stable when stored and used as directed.

Conditions to avoid:

Elevated temperatures and sources of ignition. Incompatible materials: Oxidising agents.

Hazardous decomposition products:

Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions:

No known hazardous reactions

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

ACUTE EFFECTS

Inhalation: Material may be an irritant to mucous membranes and respiratory tract.

Skin contact:

Contact with skin will result in irritation.

Ingestion:

Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact:

An eye irritant. Exposure to the dust may cause discomfort due to particulate nature. May cause physical irritation to the eyes.

NFK Glazing & Industrial Supplies

www.nfk.com.au

- 28 Devlan Street, Mansfield, QLD 4122
- 07 3343 3377
- Sales@nfk.com.au

 42 Tacoma Circuit, Canning Vale, WA 6155

08 9455 3866

🔁 wasales@nfk.com.au

ACUTE TOXICITY

Inhalation:

This material has been classified as not hazardous for acute inhalation exposure. Acute toxicity estimate (based on ingredients): LC50 > 5.0 mg/L for dust.

Skin contact:

This material has been classified as not hazardous for acute dermal exposure. Acute toxicity estimate (based on ingredients): LD50 > 2,000 mg/Kg bw

Ingestion:

This material has been classified as not hazardous for acute ingestion exposure. Acute toxicity estimate (based on ingredients): LD50 > 2,000 mg/Kg bw

Corrosion/Irritancy:

Eye: this material has been classified as a Category 2 Hazard (reversible effects to eyes).

Skin:

this material has been classified as a Category 2 Hazard (reversible effects to skin).

Sensitisation:

Inhalation: this material has been classified as not a respiratory sensitiser. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard:

This material has been classified as not an aspiration hazard.

Specific target organ toxicity (single exposure):

This material has been classified as not a specific hazard to target organs by a single exposure.

CHRONIC TOXICITY

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity:

This material has been classified as non-hazardous.

NFK Glazing & Industrial Supplies

www.nfk.com.au

28 Devlan Street, Mansfield, QLD 4122

07 3343 3377

Sales@nfk.com.au

 42 Tacoma Circuit, Canning Vale, WA 6155

08 9455 3866

🔁 wasales@nfk.com.au

Reproductive toxicity (including via lactation):

This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure):

This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard:

This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

Chronic aquatic hazard:

This material has been classified as not hazardous for chronic aquatic exposure. Nonrapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log Kow < 4.

Ecotoxicity in the soil environment:

This material has been classified as non-hazardous.

Ecotoxicity to terrestrial vertebrates:

This material has been classified as non-hazardous.

Ecotoxicity to terrestrial invertebrates:

This material has been classified as non-hazardous.

Ecotoxicity:

No information available.

Persistence and degradability:

No information available.

NFK Glazing & Industrial Supplies

www.nfk.com.au

28 Devlan Street, Mansfield, QLD 4122

07 3343 3377

🖻 sales@nfk.com.au

 42 Tacoma Circuit, Canning Vale, WA 6155

08 9455 3866

🔄 wasales@nfk.com.au

Bioaccumulative potential:

No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances) The Stockholm Convention (Persistent Organic Pollutants) The Rotterdam Convention (Prior Informed Consent) Basel Convention (Hazardous Waste) International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements: NZ EPA Status:

All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIOC).

AIICS Status:

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC).

EPA Group Standard:

HSR002544 - Construction Products (Subsidiary Hazard) Group Standard 2020

16. OTHER INFORMATION

Reason for issue: First Issue

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since the company cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for the product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

NFK Glazing & Industrial Supplies	28 Devlan Street, Mansfield, QLD 4122	42 Tacoma Circuit, Canning Vale, WA 6155
	© 07 3343 3377	08 9455 3866
www.nfk.com.au	🖻 sales@nfk.com.au	🖻 wasales@nfk.com.au