

## **NFK GLAZING & INDUSTRIAL SUPPLIES**

Specialist Suppliers of Quality Glazing Tools & Architectural Hardware



A longer version of the DSZ2-900, this 1200kg SWL rig is packed with features that ensure it will cope with heavy lifting and high repetition workloads. Designed and tested to lift more than twice its rated capacity on only one of the two independent vacuum circuits, the safety margin is theoretically four times the SWL. Six extension arms can be quickly installed and connected to create numerous lifting configurations.

Some of the unique features of this rig include:

- Dual vacuum pumps per circuit for quick attachment.
- Ability to charge and operate at the same time.
- Dual locking pins for the tilt mechanism.
- Oversized bearing packed slew ring for reduced resistance when rotating heavy glass.
- Cabled remote, allows for easy attachment / release on large sheets.
- Quick change & adjustable angle of the lifting eye.

Min Glass Size	900mm x 800mm (at 300kg capacity) / 1600mm x 1050mm (at 750kg capacity) / 2700mm x 1700mm (at 1200kg capacity)
Min Glass Width	800mm
Max Glass Size	2000mm x 3000mm (with 6 cups on main frame) / 3210mm x 6000mm (with extension arms)
Lift Capacity	1200kg
<b>Total Rig Weight</b>	180kg
Rig Size	1500mmL x 1100mmW x 250mmD / 2600mmL x 1580mmW x 250mmD (with extension arms)
Tilt	Manual - 90 degrees (available with hydraulic tilt assist to hold load at any angle)
Rotate	Manual - 360 degrees unlimited, locks in every 90 degrees



